

Python Cron

How to Run a Python Script in a Cron Scheduler in a Specific Anaconda Virtual Environment

To run a Python script in a specific Anaconda virtual environment using a cron scheduler, follow these steps:

1. **Create a Shell Script:** Write a shell script to activate the virtual environment and run your Python script. Save this script, for example, as `run_script.sh`:

...

```
#!/bin/bash
source /path/to/anaconda/envs/your_env_name/bin/activate
python /path/to/your_script.py
deactivate
...
```

Replace `/path/to/anaconda/envs/your_env_name/` with the actual path to your Anaconda environment and `/path/to/your_script.py` with the path to your Python script.

1. **Make the Script Executable:** Give the script execute permissions:

...

```
chmod +x /path/to/run_script.sh
...
```

1. **Edit the Crontab:** Open the crontab file to schedule your script:

...

```
crontab -e
...
Add a cron job entry to run your script at the desired schedule. For
example, to run it every hour, you would add:
...
0 * * * * /path/to/run_script.sh
...
```

This example runs the script at the beginning of every hour.

1. **Save and Exit:** Save the crontab file and exit the editor. The cron job is now scheduled to run your script in the specified Anaconda virtual environment.

Note: The `source` command is a Linux shell command used to load a script into the current shell session. It ensures that the environment is set up properly before executing the next commands.