Containerized Linux Print Server using Octoprint - the long way

The long way is for if you care about the technical steps and want to reproduce it yourself. See the short way to just get the LXC Octoprint image and get up and running as easy as possible.

The primary purpose of the article is to bookmark and reference my efforts to get Octoprint as opposed to Octopi, up and running on a repurposed redundant HP Laptop.

It might not be obvious why we want to do all of this, so let me start by explaining why all this effort was undertaken. So typically we would run Octopi instead, so Octorpint on a raspberry Pi. The issue with this is that due to chip shortages Pi's are now scarce and very expensive and quite framkly, mine has become slow and frustrating, so running this on a Linux PC is just orders of magnitude faster and more reliable, the issue is that Octoprint only supports one printer at a time, so if we can containerize them, we can keep on expanding until we run our of USB ports, or hardware resources, RAM, CPU and disk space. One instance of Octoprint on my 8 year old HP-Pavilion executes gcode processing about 100 times faster than my Pi 3B and the webcams just never glitch or hang, not to mention print fails because a Pi overheated or stop communicating.

This should be straightforward, how hard can it be, right. I thought so too, but days later I realized that this has to be revisited and documented as I probably will not remember most if what was done by the next time I have to repeat this process.

The basic steps to complete the process were as follow:

- Setup The Base Linux OS on the Laptop
- Install and configure LXD/LXC(Linux Containers)
- Pass Through and set up the printer connection
- Pass through and set up the webcam connection
- Start up and set up Octprint in the container

Setup The Base Linux OS on the Laptop

- Download Ubuntu 22.04 LTS ¹⁾
- Create a bootable ISO Using Rufus^{2) 3)}
- Boot from the ISO and install Ubuntu
- Create a Bridge for LXC(Linux Containers)
- Create a partition on Linux that LXD can use as a storage pool

Create a Bridge for LXC(Linux Containers)

The default config typically looks like this:

```
root@hp-linux:~# nano /etc/netplan/00-installer-config.yaml
# This is the network config written by 'subiquity'
network:
    ethernets:
        enol:
            dhcp4: true
    version: 2
```

Amend as folow to add a bridge called br0 to the config.

```
root@hp-linux:~# cat /etc/netplan/00-installer-config.yaml
# This is the network config written by 'subiquity'
network:
    ethernets:
    enol: {}
    bridges:
    br0:
        dhcp4: true
        interfaces:
            - enol
            #gateway4: 192.168.0.1
    version: 2
```

Adding a bridge allows lxc to assign network accessible DHC assigned IP addresses to the containers, i.e your container will look like regular machines on the network with similar ip addresses to other systems on the router. That will allow you to connect to octoprint using the ip or host name.



Create a partition on Linux that LXD can use as a storage pool

This step basically aims to utilize the remaining disk space that was not allocated by the ubuntu install. The HP system happens to have more that 1TiB of storage and the Linux base OS install only allocated 98GiB by default.

Lots of googling and many articles later ^{4) 5)} I started with a few commands to asses what is available and how to partition that for use by LXD.

```
root@hp-linux:~# fdisk -l /dev/sda
Disk /dev/sda: 1.82 TiB, 2000398934016 bytes, 3907029168 sectors
Disk model: ST2000LM003 HN-M
Units: sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 4096 bytes
I/O size (minimum/optimal): 4096 bytes / 4096 bytes
Disklabel type: gpt
Disk identifier: 1D2EE2A6-79C5-4DBD-B799-42B48F45F62E
```

Device	Start	End	Sectors	Size	Туре
/dev/sdal	2048	2203647	2201600	1G	EFI System
/dev/sda2	2203648	6397951	4194304	2G	Linux filesystem
/dev/sda3	6397952	3907026943	3900628992	1.8T	Linux filesystem

Command	Description
pvs	Display information about physical volumes
lvs	Display information about logical volumes
vgs	Display information about volume groups
pvdisplay	Display various attributes of physical volume(s)
lvdisplay	Display information about a logical volume
vgdisplay	Display volume group information
lvmdiskscan	List devices that may be used as physical volumes

Using the commands above to discover what space is available to assign to the lxc storage pool.

```
root@hp-linux:~# pvs
 PV
             VG
                       Fmt Attr PSize PFree
  /dev/sda3 ubuntu-vg lvm2 a-- <1.82t 735.96g
root@hp-linux:~# vgs
            #PV #LV #SN Attr
 VG
                               VSize VFree
  ubuntu-vg
             1
                 2
                      0 wz--n- <1.82t 735.96g
root@hp-linux:~# lvs
  LV
            VG
                      Attr
                                 LSize
                                         Pool Origin Data% Meta% Move Log
Cpy%Sync Convert
            ubuntu-vg -wi-ao----
                                   1.00t
 lv-lxc
  ubuntu-lv ubuntu-vg -wi-ao---- 100.00g
root@hp-linux:~# pvdisplay
  --- Physical volume ---
 PV Name
                        /dev/sda3
 VG Name
                        ubuntu-vg
                        <1.82 TiB / not usable 4.00 MiB
 PV Size
 Allocatable
                        yes
 PE Size
                        4.00 MiB
 Total PE
                        476150
                        188406
 Free PE
 Allocated PE
                        287744
 PV UUID
                        rvz2ag-hDP0-Yb91-eCr5-P01K-vs1K-Le7W4u
root@hp-linux:~# vgdisplay
  --- Volume group ---
 VG Name
                        ubuntu-vg
 System ID
  Format
                        lvm2
 Metadata Areas
                        1
 Metadata Sequence No
                        3
                        read/write
 VG Access
 VG Status
                        resizable
 MAX LV
                        0
                        2
 Cur LV
```

Open LV 2 Max PV 0 Cur PV 1 Act PV 1 VG Size <1.82 TiB PE Size 4.00 MiB Total PE 476150 287744 / <1.10 TiB Alloc PE / Size Free PE / Size 188406 / 735.96 GiB VG UUID Dfph05-yeK8-Pkrb-JZh3-TMEU-jLF4-4pn1WY root@hp-linux:~# lvdisplay --- Logical volume ---LV Path /dev/ubuntu-vg/ubuntu-lv LV Name ubuntu-lv VG Name ubuntu-vq LV UUID lupg0H-eV6M-l5YN-UjNV-j75K-P55e-a7hkeg LV Write Access read/write LV Creation host, time ubuntu-server, 2023-05-12 10:52:34 +0000 LV Status available # open 1 LV Size 100.00 GiB Current LE 25600 Segments 1 Allocation inherit Read ahead sectors auto - currently set to 256 Block device 253:0 --- Logical volume ---LV Path /dev/ubuntu-vg/lv-lxc LV Name lv-lxc VG Name ubuntu-vg LV UUID b9oWe9-UBQg-yQ3R-Io3F-XcoY-lUm3-cy8GtK LV Write Access read/write LV Creation host, time hp-linux, 2023-05-12 12:24:45 +0000 LV Status available # open 1 LV Size 1.00 TiB 262144 Current LE Segments 1 Allocation inherit Read ahead sectors auto - currently set to 256 Block device 253:1



The two commands used to set up the spare disk space was:

```
root@hp-linux:~# lvcreate -L 1T -n lv-lxc ubuntu-vg
root@hp-linux:~# mkfs.ext4 /dev/ubuntu-vg/lv-lxc
```

The first command creates a local volume of 1TiB names lvlxc in the ubuntu-vg.

The second command creates an ext4 filesystem on the volume.

Using df and lsblb to initially inspect what we can see:

root@hp-linux:~# df -h					
Filesystem	Size	Used	Avail	Use%	Mounted on
tmpfs	779M	1.7M	778M	1%	/run
/dev/mapper/ubuntuvg-ubuntulv	98G	12G	82G	13%	/
tmpfs	3.9G	0	3.9G	0 %	/dev/shm
tmpfs	5.0M	0	5.0M	0%	/run/lock
/dev/sda2	2.0G	272M	1.6G	15%	/boot
/dev/sda1	1.1G	6.1M	1.1G	1%	/boot/efi
tmpfs	1.0M	0	1.0M	0 %	
/var/snap/lxd/common/ns					
tmpfs	779M	4.0K	779M	1%	/run/user/0

No new mounted filesystem, but in the block devices we now have ubuntu-vg-lv-lxc with 1TiB of space assigned.

root@hp-linu	ux:~# lsbl	k						
NAME			MAJ:MIN	RM	SIZE	R0	TYPE	MOUNTPOINTS
loop0			7:0	0	63.3M	1	loop	/snap/core20/1879
loop1			7:1	0	73M	1	loop	/snap/core22/617
loop2			7:2	0	111.9M	1	loop	/snap/lxd/24322
loop3			7:3	0	53.2M	1	loop	/snap/snapd/19122
loop4			7:4	0	73.1M	1	loop	/snap/core22/634
loop5			7:5	0	55.6M	1	loop	/snap/core18/2745
loop6			7:6	0	108.5M	1	loop	/snap/lxdmosaic/247
loop7			7:7	0	63.5M	1	loop	/snap/core20/1891
sda			8:0	0	1.8T	0	disk	
—sda1			8:1	0	1G	0	part	/boot/efi
—sda2			8:2	0	2G	0	part	/boot
∟sda3			8:3	0	1.8T	0	part	
-ubuntu-	-vg-ubuntu	lv	253:0	0	100G	0	lvm	1
Lubuntu-	-vg-lvlx	с	253:1	0	1T	0	lvm	
sr0			11:0	1	1024M	0	rom	
root@hp-linux:~# lvs								
LV	VG	Attı	r I	LSiz	ze Poo	ol ()rigin	n Data% Meta% Move Log

Cpy%Sync Convert

lv-lxc ubuntu-vg -wi-ao---- 1.00t

We can also look at the mountpoints for the block devices like this:

<pre>root@hp-linux:~# lsblk -o NAME</pre>	NAME, FSTYPE, FSTYPE	LABEL,SIZE,MOUNTPOINT	SIZE	
MOUNTPOINT				
loop0	squashfs		63.3M	
/snap/core20/1879				
loop1	squashfs		73M	
/snap/core22/617				
loop2	squashfs		111.9M	
/snap/lxd/24322				
loop3	squashfs		53.2M	
/snap/snapd/19122				
loop4	squashfs		73.1M	
/snap/core22/634				
loop5	squashfs		55.6M	
/snap/core18/2745				
loop6	squashfs		108.5M	
/snap/lxdmosaic/247				
loop7	squashfs		63.5M	
/snap/core20/1891				
sda			1.8T	
—sda1	vfat		1G	
/boot/efi				
—sda2	ext4		2G	/boot
L_sda3	LVM2_member		1.8T	
└─ubuntuvg-ubuntulv	ext4		100G	/
└─ubuntuvg-lvlxc	zfs_member	<pre>lxd_storage_pool_default</pre>	1T	
sr0			1024M	



lvdisplay gives us the path to the storage pool required
for the next steps in LV Path that point to /dev/ubuntuvg/lv-lxc

Install and configure LXD/LXC(Linux Containers)

- Install the latest stable version of LXD
- Initialise LXD
 - \circ Specify the Bridge for Use that was set up in the OS setup section
 - $\circ\,$ Point the storage pool to the partition created previously
- Create and launch a container for octoprint

Install the latest stable version of LXD

At the time of writing this, see file date below right, LXD 5.0 was the stable release candidate, we want ti make sure to run that. My distribution uses snap, so using snap to check versions installed you can run snap list.

```
root@hp-linux:~# snap list
                                             Publisher
Name
         Version
                         Rev
                               Tracking
                                                         Notes
                               latest/stable canonical∕
core18
          20230426
                         2745
                                                        base
                               latest/stable canonical base
core20
          20230503
                         1891
         20230503
                         634
                               latest/stable canonical/ base
core22
lxd
         5.0.2-838e1b2 24322 5.0/stable
                                             canonical∕
                               latest/stable turtle0x1
lxdmosaic 0+git.c6f53f3f 247
                               latest/stable canonical/ snapd
         2.59.2
snapd
                         19122
```

If you don't have a stable candidate, it can be removed and reinstalled as follow:

```
root@hp-linux:~# snap remove lxd
root@hp-linux:~# snap install lxd --channel=5.0/stable
```

Initialise LXD

The next step is to i daemon

Default SSL material locations
ca-base /etc/ssl/certs
crt-base /etc/ssl/private

See:

https://ssl-config.mozilla.org/#server=haproxy&server-version=2.0.3&config=i
ntermediate

```
ssl-default-bind-ciphers ECDHE-ECDSA-AES128-GCM-SHA256:ECDHE-RSA-
AES128-GCM-SHA256:ECDHE-ECDSA-AES256-GCM-SHA384:ECDHE-RSA-AES256-GCM-
SHA384:ECDHE-ECDSA-CHACHA20-POLY1305:ECDHE-RSA-CHACHA20-POLY1305:DHE-RSA-
AES128-GCM-SHA256:DHE-RSA-AES256-GCM-SHA384
ssl-default-bind-ciphersuites
TLS AES 128 GCM SHA256:TLS AES 256 GCM SHA384:TLS CHACHA20 POLY1305 SHA256
```

```
ssl-default-bind-options ssl-min-ver TLSv1.2 no-tls-tickets
```

defaults

log	global	
mode	http	
option	httplog	
option	dontlogr	null
timeout	connect	5000
timeout	client	50000
timeout	server	50000

```
errorfile 400 /etc/haproxy/errors/400.http
errorfile 403 /etc/haproxy/errors/403.http
errorfile 408 /etc/haproxy/errors/408.http
errorfile 500 /etc/haproxy/errors/500.http
errorfile 502 /etc/haproxy/errors/502.http
errorfile 503 /etc/haproxy/errors/503.http
errorfile 504 /etc/haproxy/errors/504.http
```

frontend public

bind :::80 v4v6
use_backend webcam if { path_beg /webcam/ }
default_backend octoprint

backend octoprint

option forwardfor server octoprint1 127.0.0.1:5000

backend webcam

http-request replace-path /webcam/(.*) /\1
server webcam1 127.0.0.1:8080

</code>

- restart the haproxy service
- check the status of the service for any error messages after the edits

1)

https://ubuntu.com/download/server

2)

https://rufus.ie/en/

https://softwaresupply.net/kb/how-to-create-a-bootable-usb-stick/?gclid=EAIaIQobChMIh_qe98L8_gIVI Gt9Ch0FcwL7EAAYASAAEgJUj_D_BwE

https://linuxopsys.com/topics/check-unallocated-space-linux#:~:text=Unallocated%20space%20mean s%20that%20the,a%20particular%20drive%20or%20partition.

https://askubuntu.com/questions/1029040/how-to-manually-mount-a-partition